



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Vacuum gate valve, Series 121, DN 200 (ID 8")
Ordering No. 12146-JA34

Description

Flange	JIS 200
Actuator	Pneumatic, double acting – with solenoid valve
Feedthrough	Shaft feedthrough

Technical data

Leak rate	– Valve body – Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹ $< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-7}$ mbar to 1.6 bar (abs)
Differential pressure on the gate		≤ 1.6 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		12 000 ls ⁻¹
Cycles until first service		100 000 (unheated and under clean conditions)
Temperature (Maximum values: depending on operating conditions and sealing materials)	– Valve body – Actuator – Solenoid valve	≤ 120 °C ≤ 80 °C ≤ 50 °C
Heating and cooling rate		30 °C h ⁻¹
Material	– Valve body – Mechanism	EN AC-42100 (3.2371) EN AW-6082 (3.2315)
Seal	– Bonnet – Gate – Actuator	FKM (Viton®) FKM (Viton®), O-ring FKM (Viton®), NBR (BUNA N®)
Mounting position		any
Volume of pneumatic actuator		0.9 l / 0.032 ft ³
Compressed air min. – max. overpressure		4–7 bar / 58–102 psi
Compressed air connection		G 1/8" (1/8" NPT for USA)
Actuation time	– closing – opening	3.0 s 3.0 s
Weight		14.1 kg / 31 lbs

Created by: SON	Release date: 2013-06-13	1 of 2
Modified by:	Release date:	233627EA



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Vacuum gate valve, Series 121, DN 200 (ID 8")
Ordering No. 12146-JA34

Behavior in case of compressed
air pressure drop

- Valve closed
- Valve open

- valve remains closed
- undefined

Behavior in case of power failure

- Valve closed
- Valve open

- valve remains closed
- valve closes

Electrical connections

Solenoid valve

Type

4/2 way

Voltage

Defined by order

