



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet

**All-Metal Gate Valve, Series 48.1, DN 40 (ID 1 1/2")**

**OSL-Article No. 48132-CE05**


### Description

Flange	DN 40 CF-F
Actuator	manual actuator with position indicator 200°C
Feedthrough	bellows

### Technical data

Leak rate	
- To the outside	$< 1 \cdot 10^{-10}$ mbar ls <sup>-1</sup>
- Seat	$< 1 \cdot 10^{-10}$ mbar ls <sup>-1</sup>
Molecular flow conductance	90 ls <sup>-1</sup>
Pressure range	XUHV to 2 bar (abs)
Test pressure	1 bar
Differential pressure on the gate	
- in closing and opening direction	2 bar
Max. differential pressure at opening	
- in closing and opening direction	1 bar
Cycles until first service	20'000
Bake-out temperature	
- Valve	300°C
- Actuator	140°C
- Position indicator	200°C
Heating and cooling rate	50°C h <sup>-1</sup>
Material	
- Body	1.4435, AISI 316 L
- Flange	1.4435 ESU, AISI 316 L ESR
- Gate	1.4435, AISI 316 L
- Mechanism (in contact with media)	1.4435, AISI 316 L
- Bellows	1.4435, AISI 316 L
Seal	
- Bonnet	metal
- Gate	metal
Mounting position	any
Radiation resistance	
- Valve	10 <sup>8</sup> Gy (10 <sup>10</sup> rad)
- Actuator, position indicator	10 <sup>5</sup> Gy (10 <sup>7</sup> rad)
Turns per stroke	22
Dimensional drawing	204564
Weight	5.7 kg / 14 lbs

Wiring diagram:



Lo = position indicator «open»  
Lg = position indicator «closed»

Created by: Kurt Sonderegger	Release date: 01.06.04	Page 1 of 1
Modified by::	Release date:	<b>250842EA</b>