

Product data sheet

Vacuum gate valve, Series 08.1, DN 63 (ID 2½") Ordering No. 08136-FA24

Description

Flange DN 63 Flat flanges with O-ring grooves

Actuator pneumatic, double acting

– with position indicator

Feedthrough Shaft feedthrough

Technical data

Leak rate - Valve body $< 5 \cdot 10^{-9}$ mbar Is⁻¹

– Valve seat < 1 · 10⁻⁹ mbar Is⁻¹

Pressure range $1 \cdot 10^{-7}$ mbar to 1.6 bar (abs)

Differential pressure on the gate \leq 1.6 bar

Differential pressure at opening \leq 30 mbar

Conductance (molecular flow) 1 000 ls⁻¹

Cycles until first service 200 000 (unheated and under clean conditions)

sealing materials)

Heating and cooling rate 50 °C h⁻¹

Material (main components) – Valve Body EN AW-5083 (3.3547), EN AW-6061 (3.3211)

Mechanism
 AISI 304 (1.4301)

Seal – Bonnet FKM (Viton®) – Gate FKM (Viton®)

- Shaft feedthrough FKM (Viton®)

Mounting position any

Volume of pneumatic actuator 0.16 l / 0.0056 ft³

Compressed air 4-7 bar / 58-102 psi

min. - max. overpressure

Compressed air connection M5 (10-32 UNF suitable)

Actuation time – closing 1.5 s

opening1.5 s

Weight 2.3 kg / 5.1 lbs

Created by: MAEM	Release date: 2013-06-10	1 of 2
Modified by:	Release date:	265991EA



Product data sheet

Vacuum gate valve, Series 08.1, DN 63 (ID 2½") Ordering No. 08136-FA24

Behavior in case of compressed

air pressure drop

Valve closedValve open

valve remains closed

undefined

Behavior in case of power failure

Valve closedValve open

depending on customer installation


depending on customer installation

Position indicator

Type Micro switch

Voltage \leq 250 V AC, \leq 50 V DC

Current max. \leq 2 A, \leq 1.2 A



Created by: MAEMRelease date: 2013-06-102 of 2Modified by:Release date:265991EA