



VAT Vakuumventile AG  
CH-9469 Haag, Schweiz

## Product data sheet

**HV gate valve, Series 110, DN 160 (ID 6'')**  
**Ordering No. 11044-JE01**

### Description

Flange	JIS 160
Actuator	Manual, handwheel
Feedthrough	Bellows

### Technical data

Leak rate	- Valve body	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
	- Valve seat	$< 1 \cdot 10^{-9}$ mbar ls <sup>-1</sup>
Pressure range		$1 \cdot 10^{-8}$ mbar to 1.6 bar (abs)
Differential pressure on the gate		$\leq 1.6$ bar
Differential pressure at opening		$\leq 30$ mbar
Conductance (molecular flow)		5880 ls <sup>-1</sup>
Cycles until first service		200 000 (unheated and under clean conditions)
Temperature (Maximum values: depending on operating conditions and sealing materials)	- Valve body	$\leq 150$ °C
	- Actuator	$\leq 80$ °C
Heating and cooling rate		50 °C h <sup>-1</sup>
Material (main components)	- Valve body	AISI 304 (1.4301)
	- Mechanism	AISI 316L (1.4404)
	- Bellows	AISI 633 (AM350)
Seal	- Bonnet	FKM (Viton <sup>®</sup> )
	- Gate	FKM (Viton <sup>®</sup> ), vulcanized
	- Actuator	FKM (Viton <sup>®</sup> ), NBR
Mounting position		any

Created by: MAEM	Release date: 2013-03-27	1 of 1
Modified by:	Release date:	<b>285740EA</b>