



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Vacuum angle valve, Series 244, DN 25 (ID 1 ")
Ordering No. 24428-KE32-0001

Description

Flange	ISO-KF 25
Actuator	Pneumatic, single acting with opening spring – with solenoid valve – without position indicator
Feedthrough	Shaft feedthrough

Technical data

Leak rate	– Valve body – Valve seat	$< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$ $< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$
Pressure range		$1 \cdot 10^{-7} \text{ mbar}$ to 5 bar (abs)
Differential pressure on the plate	– In opening direction – In closing direction	$\leq 2 \text{ bar}$ $\leq 5 \text{ bar}$
Differential pressure at opening		$\leq 1 \text{ bar}$ $\leq 3 \text{ bar}$ with reduced cycle lifetime (min. 450 000)
Conductance (molecular flow)		14 ls^{-1}
Closing time		$\leq 0.15 \text{ sec.}$
Cycles until first service (Tmax 80°C, differential pressure max. 1 bar)		3 million
Admissible Temperature	– Valve body – Actuator – Solenoid valve	$\leq 150 \text{ °C}$ $\leq 120 \text{ °C}$ $\leq 80 \text{ °C}$
Material	– Valve body – Actuator – Plate – Shaft feedthrough	AISI 304 (1.4301) Aluminum AISI 316L (1.4435 ESU) Stainless Steel
Seal	– Bonnet O-ring – Plate O-ring – Actuator O-ring	FKM (Viton®) FKM (Viton®) FKM (Viton®)
Weight		0.6 kg / 1.32lbs
Mounting position		any
Volume of pneumatic actuator		0.011 l / 0.0004 ft ³
Compressed air min. – max. overpressure		4 – 8 bar / 60 – 115 psi
Compressed air connection		M5 female (10-32 UNF suitable)

Created by: R. Walser	Release date: 2013-07-11	Page 1 of 2
Modified by:	Release date:	603287EA



VAT Vakuumventile AG
CH-9469 Haag, Schweiz


Product data sheet

Vacuum angle valve, Series 244, DN 25 (ID 1 ")
Ordering No. 24428-KE32-0001

Electrical connections

Solenoid valve

Type	3/2-way
Voltage	See solenoid
Power	See solenoid
Connector	Rectangle plug, Type B (DIN standard)
Cable	Ø6 – 8 mm



Wiring diagram