



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve, Series 140, DN 250 (ID 10'')
Ordering No. 14048-TE01

Description

Flange	ASA-LP 250
Actuator	Manual, handwheel
Feedthrough	Rotary feedthrough

Technical data

Leak rate	- Valve body	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
	- Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-8}$ mbar to 1.2 bar (abs)
Differential pressure on the gate		≤ 1.2 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		19 995 ls ⁻¹
Cycles until first service	- Unheated and under clean conditions	200 000
Temperature (Maximum values: depending on operating conditions and sealing materials)	- Valve body	≤ 150 °C
	- Manual actuator	≤ 80 °C
Heating and cooling rate		50 °C h ⁻¹
Material (main components)	- Valve body	AISI 304 (1.4301)
	- Mechanism	AISI 304 (1.4301), AISI 316L (1.4404)
Seal	- Bonnet	FKM (Viton®), O-ring
	- Gate	FKM (Viton®), O-ring
	- Actuator	FKM (Viton®), NBR
Mounting position		any
Weight		60.0 kg / 132.0 lbs

Created by: JOM	Release date: 2013-09-20	1 of 1
Modified by:	Release date:	604215EA