



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet No. 286944EB

Vacuum Angle Valve, Series 244, DN 63 (ID 2 1/2 ")

Ordering No. 24436-QA11 or 24436-QE11

Description

Flanges	ISO-K63
Actuator	- pneumatic, single acting with closing spring - without solenoid - without position indicator
Feedthrough	shaft feedthrough

Technical data

Leak rate	- body & valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Molecular flow conductance		160 ls ⁻¹
Pressure range		$1 \cdot 10^{-7}$ mbar to 4 bar, abs
Differential pressure on the plate:		
- in opening direction		≤ 2 bar
- in closing direction		≤ 5 bar
Differential pressure at opening:		
- in opening direction		≤ 1 bar
- in closing direction		≤ 1 bar
		≤ 3 bar with reduced cycle lifetime (min. 450 000) (compressed air pressure > 5 bar required to open)
Closing time		$\leq 0,7$ sec.
Admissible temperature:	- valve body, actuator	0°C - 120°C
Cycles until first service		3 million (T _{max} 80°C, differential pressure max. 1 bar)
Material:		
	- valve body	24436-QA11 Aluminum (EN AW-6060)
	- pneumatic actuator	Aluminum
	- valve plate	AISI 316L(1.4435 ESU)
	- feedthrough	Aluminum(EN AW 6082)
	- bonnet & plate seal	Viton
	- actuator o-rings	Viton
		24436-QE11 Stainless Steel (1.4301)
		Aluminum
		AISI 316L(1.4435 ESU)
		Stainless Steel (1.4301)
		Viton
		Viton
Weight		4 kg / 8.8 lbs 5.5 kg / 12.1 lbs
Mounting position		any
Volume of air cylinder		0,112 l / 0,0040 ft ³
Compressed air pressure for pneumatic		4 - 8 bar / 60 - 115 psi
Compressed air connection		female 1/8" (ISO/NPT)

Created by: R. Walser	Release date: 2010-12-02	Page 1 of 1
Modified by: R. Walser	Release date: 2011-04-14	286944EB