



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

HV gate valve, Series 140, DN 400 (ID 16'')
Ordering No. 14052-PE08

Description


Flange	ISO-F 400
Actuator	Manual, handwheel – with position indicator
Feedthrough	Rotary feedthrough

Technical data

Leak rate	– Valve body	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
	– Valve seat	$< 1 \cdot 10^{-9}$ mbar ls ⁻¹
Pressure range		$1 \cdot 10^{-8}$ mbar to 1.2 bar (abs)
Differential pressure on the gate		≤ 1.2 bar
Differential pressure at opening		≤ 30 mbar
Conductance (molecular flow)		52 000 ls ⁻¹
Cycles until first service	– Unheated and under clean conditions	200 000 (valve in horizontal position) 50 000 (valve in vertical position)
Temperature (Maximum values: depending on operating conditions and sealing materials)	– Valve body	≤ 150 °C
	– Actuator	≤ 80 °C
	– Position indicator	≤ 80 °C
Heating and cooling rate		50 °C h ⁻¹
Material (main components)	– Valve body	AISI 304 (1.4301)
	– Mechanism	AISI 304 (1.4301)
Seal	– Bonnet	FKM (Viton®), O-ring
	– Gate	FKM (Viton®), O-ring
	– Actuator	NBR
Compressed air connection		G $\frac{1}{8}$ " (½" NPT for USA)
Mounting position		horizontal (vertical with restriction)
Weight		141 kg / 311 lbs

Position indicator

Type	Micro switch	
Voltage	≤ 250 V AC	≤ 50 V DC
Current max.	≤ 5 A	≤ 3 A



Wiring diagram

Created by: MAEM	Release date: 2013-04-15	1 of 1
Modified by:	Release date:	601390EA